




















Dymonic[®] ***FC***

Standard Colors

Colors shown are approximate and may not reflect the shade precisely. Different lighting conditions can influence color appearance, for truer color please view in daylight. Colors are not stocked in all available package types. Minimum order quantities will apply for custom colors and alternative packaging. For more information, please contact Tremco Customer Service.

	PRECAST WHITE
	ANODIZED ALUMINUM
	IVORY
	OFF WHITE
	ALMOND
	STONE
	LIMESTONE
	GRAY
	NATURAL CLAY
	BUFF
	ALUMINUM STONE
	BEIGE
	LIGHT BRONZE
	REDWOOD TAN
	HARTFORD GREEN
	BRONZE
	DARK BRONZE
	BLACK
	WHITE

TREMCO®

Dymonic® FC

Dymonic® FC

High-Performance, Fast-Curing, Single-Component, Hybrid Sealant

Dymonic® FC is a high-performance, fast-curing, single-component, low modulus, hybrid sealant formulated with proprietary silane end-capped polymer technology.

Applicable Standards

ASTM C 920 Type S, Grade NS, Class 35, Use NT, M, A and O; ASTM C 1248; CAN/CGSB-19.13-M87;
U.S. Federal Specification TT-S-00230C, Class A, Type II;
Meets AAMA 808.3-10; UL 2079 (ASTME 1966), CAN-4-S115M.

Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906
220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213
1451 Jacobson Avenue, Ashland, OH 44805 // Phone: 419.289.2050 // 800.321.6457

1117/DFCSD